



# X400 LUSTER SHIELD



## Product Info Sheet

Issued: 25th July 2014  
Document #: NZ 400 PIS/1  
Page 1 of 1



**Breathable, tough, attractive, easy care, long lasting, low slip satin coating for polished or trowel finished concrete slabs.**

### Description & Uses

X400 is a high-quality, proprietary acrylic formula dispersion that when applied and fully dried / cured, develops into a strong, durable, flexible, and breathable film-coating which adheres tenaciously to clean, bare concrete surfaces, render and masonry. X400 is non-flammable, odourless, penetrating coating that will dry to a clear attractive satin finish.



### Features and Benefits

- Clear attractive satin finish
- Environmentally friendly
- Low odour - 0.0g/L VOC
- Durable
- Easily maintained
- Can be buffed to a high gloss finish.
- Easy to use, no specialist equipment needed
- Compatible with X420 High Solids Commercial Polish
- Low cost
- Repairable
- Suitable for any concrete or masonry surface
- HACCP approved



### Application

HOW TO APPLY AS A PROTECTIVE COATING:

**Note: Always start with a clean bare surface. Remove all dirt, stains, glues and previous coatings. If you don't they will be preserved for the life of the coating.**

1. Using a short nap paint roller or micro fibre applicator, apply evenly

and thinly at the rate shown on the chart. Do not over apply or allow to puddle.

2. Allow at least 24 hours to dry thoroughly. May require more drying time in high traffic areas and during damp weather.
3. May be burnished to a higher sheen with high speed machine with animal hair pad. Contact your nearest Protect-Crete office for details.

### Precautions

- Protect areas not intended for coverage as product is very difficult to remove when dry.
- When used as a coating X400 must be applied in a thin layer, otherwise the strength of the bond will be compromised. For a thicker layer apply subsequent coats 24 hours after each application.
- X400 will adhere to the first surface it meets, including dirt. If product adheres to dirt it may peel up.
- X400 has a minor almost insignificant trace of VOC. Ingestion, skin or eye contact should be avoided. Refer to MSDS.
- We recommend use of a painters mask during application.
- Do not allow water on the surface for 7 days after application.
- Do not apply to surface in full sun or if temperature outside range of 4C- 24C.

For more information visit: [www.protectcretenz.co.nz](http://www.protectcretenz.co.nz)



**PROTECT CRETE NZ Ltd**  
PO Box 10080, Rotorua Mail Centre  
Rotorua 3046  
Ph: +64 9 441 9003  
Email: [sales@protectcretenz.co.nz](mailto:sales@protectcretenz.co.nz)



**GILT EDGE INDUSTRIES**  
CHC: 03 379 7067  
AKL: 03 379 7067  
Email: [help@giltedge.co.nz](mailto:help@giltedge.co.nz)

**Technical & Sales Assistance**  
Email: [sales@giltedge.co.nz](mailto:sales@giltedge.co.nz)  
[www.giltedge.co.nz](http://www.giltedge.co.nz)