



X520 WAREHOUSE



Complete Warehouse, Retail & Display Floor Protection

Description & Uses

X520 Warehouse is a proprietary silicate silicate formulation with Densi Proof as its primary base. Applied to new and existing concrete giving excellent cure regime, water and dust proof, surface hardener and stain resistance from oils and is compatible with line marking. Densi Proof has been tested to ASTM C-67 Section 65 (ORF Method) ABRASION (DUSTING) RESISTANT TEST and showed Concrete treated with Densi-Proof is approximately four times more abrasion resistant as untreated concrete. Achieves cure results as required by NZS 3109:1997

Features and Benefits

- Single Application
- Resists oil staining
- Reduced tyre squeal
- Waterproof assistance
- Hardens surface
- Reduces dusts
- Clear invisible finish
- Environmentally friendly
- Low odour - 0.0g/L VOC
- Long lasting
- Reduces staining.
- Retards efflorescence
- Highly resistant to alkali attack
- Improves Fungus / Mildew Resistance
- Resists Freeze-Thaw Damage
- Enhances Traction Quality
- Easy and safe to apply
- UV Resistant
- User Friendly
- Non-Flammable
- Will not darken or yellow



Application

NOTE: In hot windy climates, mist-wet the surface with water and remove any puddles prior to application.

AS CURE; Apply as soon as possible after concrete's initial set for optimum cure benefit.

EXISTING; Apply to clean absorbent surface.

1. Use a pump pack type sprayer or powered non atomizing sprayer and evenly apply.
2. Ensure you do not mark the surface of new concrete

with either your feet or pressure from the spray.

3. Begin applying at the lowest level elevation. For example, walls, ramps and slopes should be applied side to side, from the bottom up.
4. Can be buffed or apply X420 Luster Keep for high shine.

RATE:

Burnished or steel troweled surface apply at a rate of 6.5m² - 8m² per litre. Broom finished or open surfaced finishes apply at a rate of 3.5m² - 6.5m² per litre.

Precautions

- Like wet concrete and some high alkali cleaning products, X520 WAREHOUSE will etch glass and discolour brushed aluminum if not removed before it dries. Mask or clean off with a wet cloth as you go.
- Do not allow X520 WAREHOUSE to dry in puddles on the concrete surface, an hour after application remove before they dry on the surface with a soft broom, water or blower.
- Always test suitability and compatibility with your next process.



For more information visit: www.protectcretenz.co.nz



PROTECT CRETE NZ Ltd
PO Box 10080, Rotorua Mail Centre
Rotorua 3046
Ph: +64 9 441 9003
Email: sales@protectcretenz.co.nz



GILT EDGE INDUSTRIES
CHC: 03 379 7067
AKL: 03 379 7067
Email: help@giltedge.co.nz

Technical & Sales Assistance
Email: sales@giltedge.co.nz
www.giltedge.co.nz