



X220 Moisture Fix[®]

SAFETY DATA SHEET

Oxtek Australia Pty Ltd
Product: X220 Moisture Fix[®]
Page 1 of 8
Date of Issue: March 2016

SECTION 1 – IDENTIFICATION OF MATERIAL AND SUPPLIER

SUPPLIER:	Protect Crete NZ Ltd.
ADDRESS:	PO Box 10080, Rotorua Mail Centre Rotorua 3046 Rotorua 3046 New Zealand.
TELEPHONE:	(+64 9) 441 9003.
AH EMERGENCY TELEPHONE:	0800 POISON (0800 764 766) (24 Hours) - New Zealand National Poisons Centre.
Email:	sales@protectcretenz.co.nz
WEB PAGE:	www.protectcretenz.co.nz
Product Name:	PROTECT CRETE [®] X220 Moisture-Fix [®] .
Proper Shipping Name:	Not applicable.
Product Use:	Inorganic binder for concrete treatment.
Manufacturer's Product Code:	Not applicable. [®]
Creation Date:	8 March 2016.
Revision Date:	Before 15 August 2016.

SECTION 2 – HAZARDS IDENTIFICATION

This product is not classified as HAZARDOUS according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, and not classified as Dangerous Goods for transport, according to the New Zealand Standard NZS 5433:2007 Transport of Dangerous Goods on Land.	
Hazard Category:	Non-Hazardous, alkaline.
Emergency Overview:	May be harmful by ingestion, and in contact with skin.
Skin Contact:	May cause slight skin irritation.
Ingestion:	May be harmful.
Eye Contact:	May be slightly irritating to eyes.
Primary Routes of Exposure:	Eyes, skin, mouth.
Risk Statements:	Not applicable.
Safety Statements:	Not applicable.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:	CAS Number:	Proportion:
Silicates (Non-Hazardous)	Proprietary	10 - < 30% w/w
Other Ingredients (Non-Hazardous)	Proprietary	< 10% w/w
Water	7732-18-5	To 100% w/w
Total		100% w/w



X220 Moisture Fix®

Oxtek Australia Pty Ltd
Product: X220 Moisture Fix®
Page 2 of 8
Date of Issue: March 2016

SAFETY DATA SHEET

SECTION 4 – FIRST AID MEASURES

First Aid Facilities Required:	Eye wash fountains and a general washing facility should be easily accessible in the immediate work area.
Inhalation:	Not expected to be an inhalation hazard. Remove victim from exposure – avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.
Skin Contact:	For gross contamination immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of running water. Immediately remove contaminated clothing and wash before reuse. If irritation develops seek medical attention.
Eye Contact:	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the New Zealand National Poisons Centre or a doctor, or for at least 15 minutes. If irritation develops seek medical attention.
Ingestion (Swallowed):	Immediately rinse out mouth with water. If swallowed DO NOT induce vomiting. Give a glass of water to drink. Never give anything by mouth to an unconscious patient. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration into the lungs. Get to a doctor or hospital quickly.
Advice to Doctor:	No specific antidote. Treat symptomatically. New Zealand National Poisons Centre can provide additional assistance for scheduled poisons.

SECTION 5 – FIRE FIGHTING MEASURES

Hazards from Combustion Products:	Product itself is not combustible.
Suitable Extinguishing Media:	Define extinguishing measures according to neighbouring conditions.
Precautions for Fire Fighting:	No special protective equipment measures required.
Hazchem Code:	Not applicable.
Flash Point:	Not applicable.
Flammability:	Product is Non-flammable according to the New Zealand Standard NZS 5433:2007 Transport of Dangerous Goods on Land. No special measures for fire and explosion protection. No dangerous decomposition products known.



X220 Moisture Fix[®]

Oxtek Australia Pty Ltd
Product: X220 Moisture Fix[®]
Page 3 of 8
Date of Issue: March 2016

SAFETY DATA SHEET

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spills:

Personal Precautions: In case of spill, particular danger of slipping on leaked/spilled product. Isolate hazard area and deny entry.

Environmental Precautions: Do not allow to enter drainage system, surface or ground water. In the event of product entering waters or drainage system, or polluting soil or plants contact the Environmental Protection Authority or your local Waste Management Authority.

Methods of cleaning up/of removing: Spilt material should be absorbed into dry, inert material (e.g. sand, vermiculite, diatomite, acid binders, universal binders, sawdust etc.), which then can be put into appropriately labelled drums. The wasted material can be disposed of by incineration (preferably high temperature) by an approved agent according to National and/or Local government regulations.

SECTION 7 – HANDLING AND STORAGE

Handling: Avoid all personal contact, including skin and eye contact and contamination of clothing. Wear protective clothing when risk of exposure occurs. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers closed at all times. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use.

Information about Fire and Explosion Protection: No special measures required.

Storage:

General: Store away from incompatible substances including acids and light alloys. Keep containers closed at all times.

Requirements for Storerooms & Receptacles: Do not use light alloy receptacles.

Unsuitable Materials for Receptacles: Aluminium, zinc, glass or ceramic.

Suitable Materials for Receptacles & Pipes: Steel or stainless steel. Use polyolefin receptacles.

Further Information about Storage Conditions: Protect from frost.



X220 Moisture Fix[®]

SAFETY DATA SHEET

Oxtek Australia Pty Ltd
Product: X220 Moisture Fix[®]
Page 4 of 8
Date of Issue: March 2016

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits:	Workplace Exposure Standards, as published by The Workplace Group of the Department of Labour: Time-weighted Average (TWA): None established for product. Short Term Exposure Limit (STEL): None established for product. The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
Engineering Controls:	Product is recommended to be applied using a spray apparatus. In outdoor application no special ventilation or breathing equipment is required. If applied indoors, extra mechanical ventilation may be required to facilitate more comfortable breathing.
Personal Protection:	<u>General protective & hygiene measures:</u> The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. <u>Respiratory protective equipment:</u> Not required. <u>Eye protection:</u> The use of face shield protection is recommended to avoid airborne particles contacting eyes and skin during spraying. Otherwise, the use of chemical goggles or safety glasses with side shield protection is recommended. <u>Hand protection:</u> Alkaline resistant gloves (e.g. Butyl, Natural Rubber Latex with small amount of Polychloroprene Latex, Polychloroprene, Nitrile, Polyvinyl Chloride or PVC, Polyvinyl Alcohol or PVAL gloves complying with AS/NZS 2161) are recommended. <u>Clothing:</u> Suitable protective clothing.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical Description/ Properties:	
Appearance:	Low viscosity liquid.
Colour:	Clear blue hue.
Odour:	Almost none.
pH:	Ca. 11.4.
Vapour Pressure:	Not available.
Vapour Density:	Not available.
Boiling Point/ Range:	> 100°C @ 760 mm Hg.
Freezing/ Melting Point:	Not available.
Solubility in Water:	Fully miscible.
Specific Gravity:	Ca. 1.10.
Flashpoint:	Not applicable.
Auto Ignition Temperature:	Product is not self-igniting.
Flammability Limits:	Not applicable.
Other Properties:	
Evaporation Rate:	Not available.
Viscosity:	Low.
Stability:	Stable under normal conditions.



X220 Moisture Fix[®]

SAFETY DATA SHEET

Oxtek Australia Pty Ltd
Product: X220 Moisture Fix[®]
Page 5 of 8
Date of Issue: March 2016

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability:	Stable at normal temperatures and pressure.
Thermal Decomposition:	No decomposition if used according to specifications.
Dangerous Reactions:	Strong exothermic reaction with acids. Reacts with light alloys to form hydrogen.
Conditions to Avoid:	Avoid contact with incompatible materials.
Materials to Avoid:	Acids, light alloys.
Hazardous Decomposition Products:	No dangerous decomposition products known.

SECTION 11 – TOXICOLOGICAL INFORMATION

Health Effects:	
Acute:	
Swallowed:	Alkaline product. May cause burning in throat and mouth. Seek medical attention.
Eye:	Slightly irritant.
Skin:	Slightly irritant.
Inhaled:	No data for product.
Mutagenicity:	No data for product.
Carcinogenicity:	No data for product.
Reproductive & Developmental Toxicity:	No data for product.
Sensitization:	No sensitizing effects known.
Acute Toxicity Data (Oral):	No data for product. On basis of ingredients, Acute Toxicity for active ingredient LD ₅₀ (Oral, rat) > 2000 mg/kg.
Acute Toxicity Data (Dermal):	No data for product.
Acute Toxicity Data (Inhalation):	No data for product.
Chronic Toxicity Data:	No data for product.

SECTION 12 – ECOLOGICAL INFORMATION

Fish Toxicity:	No data for product, on the basis of ingredients: Acute Toxicity for active ingredient LC ₅₀ (96 h, Zebra fish, Brachydanio rerio) > 1000 mg/l.
Algae Toxicity:	None available for product.
Invertebrates Toxicity:	No data for product, on the basis of ingredients, Acute Toxicity for active ingredient EC ₅₀ (48 h, Daphnia) > 1000 mg/l.
Toxicity to Microorganisms:	None available for product.
OECD Biological Degradation:	None available for product.
Information about Elimination (Persistence & Degradability):	Readily eliminable from water. Inorganic product; biotic degradation not applicable.
Ecotoxic Effects:	No toxicity after neutralization.



X220 Moisture Fix[®]

SAFETY DATA SHEET

Oxtek Australia Pty Ltd
Product: X220 Moisture Fix[®]
Page 6 of 8
Date of Issue: March 2016

SECTION 12 – ECOLOGICAL INFORMATION (CONTINUED)

Behaviour in Sewage Processing Plants:	The product is an alkaline solution. Neutralization is normally necessary before a waste water is discharged into sewage treatment plants.
General:	DO NOT DISCHARGE INTO DRAINS, WATERWAYS, SEWER OR ENVIRONMENT. Product is slightly hazardous for water. Product is fully miscible with water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Inform local authorities if this occurs.

SECTION 13 – DISPOSAL CONSIDERATIONS

Product:	Recommended that it can be disposed off with rubble after solidification following consultation with the waste disposal facility operator according to National and/or Local government regulations, pertinent authorities and adhering to the necessary technical regulations.
Uncleaned Packaging:	Recommended to be disposed of according to official regulations. Recommended cleansing agent is water, if necessary with cleansing agents.

SECTION 14 – TRANSPORT INFORMATION

General:	This material is not classified as Dangerous Goods for transport, according to the New Zealand Standard NZS 5433:2007 Transport of Dangerous Goods on Land.
UN Number:	Not applicable.
UN Proper Shipping Name:	Not applicable.
ADG Class:	Not applicable.
Packing Group:	Not applicable.
HAZCHEM Code:	Not applicable.

SECTION 15 – REGULATORY INFORMATION

HSNO:	This product is not classified as HAZARDOUS according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and therefore does not require any ERMA Register Approval Number.
NZIoC:	All ingredients present on NZIoC.
Dangerous Good:	Not applicable.
Labelling Details:	
Risk Statements:	Not applicable.
Safety Statements:	Not applicable.



X220 Moisture Fix[®]

SAFETY DATA SHEET

Oxtek Australia Pty Ltd
Product: X220 Moisture Fix[®]
Page 7 of 8
Date of Issue: March 2016

SECTION 16 – OTHER INFORMATION

Acronyms and Comments:

CAS Number:	Chemical Abstracts Service Registry Number.
EPA:	The Environmental Protection Authority (EPA) is responsible for national environmental regulatory functions currently spread across Government. It processes matters of national significance under the Resource Management Act, undertakes all functions under the HSNO Act, undertakes permitting and exemption functions under the Ozone Layer Protection Act, permitting functions relating to the import and export of hazardous waste, and advises on the development of National Environmental Standards.
ERMA:	Environmental Risk Management Authority, now replaced by EPA.
HAZCHEM:	An emergency action code of numbers and letters which gives information to emergency services.
HSNO	The Hazardous Substances and New Organisms Act is administered by the EPA, and covers all Hazardous Substances and New Organisms.
IERG:	Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB 76:2010 Standards New Zealand Handbook).
NZS:	New Zealand Standards which are available from Standards New Zealand, Private Bag 2439, Wellington 6140 New Zealand.
NZIoC:	The New Zealand Inventory of Chemicals is a database of all the hazardous chemical components of products approved under group standards. It also includes a number of non-hazardous chemical components.
SDS:	Safety Data Sheet.
STEL:	Exposure standard - short term exposure limit, a 15 minute TWA exposure which should not be exceeded at any time during a working day even if the eight-hour TWA average is within the TWA exposure standard. Exposures at the STEL should not be longer than 15 minutes and should not be repeated more than four times per day. There should be at least 60 minutes between successive exposures at the STEL. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.
TWA:	Exposure standard - time-weighted average, the average airborne concentration of a particular substance when calculated over a normal eight hour working day, for a five-day working week.
UN Number:	United Nations Number.
Issue Date:	16 August 2011.
Supersedes Issue Date:	New Issue.
Revision Information:	New Issue.
Contact Point:	Regulatory Affairs Manager.
Telephone:	(+64 9) 441 9003.
Note:	Safety Data Sheets are updated frequently. Please ensure that you have a current copy.



X220 Moisture Fix[®]

Oxtek Australia Pty Ltd
Product: X220 Moisture Fix[®]
Page 8 of 8
Date of Issue: March 2016

SAFETY DATA SHEET

SECTION 16 – OTHER INFORMATION (CONTINUED)

Disclaimer:

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of this product, and in particular how to safely handle and use this product in the workplace. Since Protect Crete NZ Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace. This SDS does not represent a guarantee for the properties of the product(s) described in terms of the legal warranty regulations. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Copyright Notice:

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from Protect Crete Pty Ltd TEL (+61 3) 9872 6172. © PROTECT CRETE PTY LTD 2011 Issue Date: 8th March 2016, Print Date: 10th March 2016.